



Specification:

1. Current rating: 1,5PIN 1.8A Max/2,3,4PIN 1A Max.
2. Dielectric withstanding voltage: 100 V(ac) for 1 min.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 100 MΩ Min.
5. Total mating force: 3.57 Kgf Max.
6. Total unmating force: 1.0 Kgf Min.
7. Temperature range: -30°C~80°C



Code	Shell Plated
_ =2	Ni Plated (50u")
_ =4	Matt Tin Plated (50u")

3	CONTACT	COPPER ALLOY T=0.15	3	Gold Flash
2	SHELL	COPPER ALLOY T=0.25	1	SEE TABLE
1	HOUSING	LCP UL94V-0	1	BLACK
NO.	PART NAME	MATERIAL	QTY	FINISH

TITLE: Micro USB 5S B Type

MODEL NO. UCB33SB30\_0-05R

WELL LONG ELECTRONIC COMPONENTS LTD.

Tel: (852)2348 9203 / (769)8398 3456

E-mail: [sales@welllong.com.hk](mailto:sales@welllong.com.hk)

APPROVED:	S. HUANG	UNIT: MM			
CHECKED:	S. HUANG	SCALE: 5:1			
DRAWN:	Angla				
DATE:	2015/05/21				
ITEM	REVISION	REV BY	DATE	DATE:	2015/05/21

GENERAL TOLERANCE

.X	±0.15
.XX	±0.10
.XXX	±0.05
ANGLE	±1°